

Technical Specifications

Repose Solid Loose Lay Vinyl™ combines a fiberglass-reinforced solid vinyl structure with a straight edge profile for enhanced stability, durability, and ease of installation.

FEATURES	SUGGESTED APPLICATIONS
<ul style="list-style-type: none"> • Up to three times faster to install than other vinyl plank flooring products • Integrated fiberglass reinforcement layer for greater dimensional stability • Naturally quiet, comfortable floor-- mitigates impact and sound transmission without additional underlayment • 100% waterproof 	Residential Homes Apartments, Condominiums Hospitality Health Care Commercial

PRODUCT DETAIL

Construction	5.0mm Solid Vinyl Flooring
Wear Layer	Standard: 22 mil/0.5mm Custom: 12 mil/0.3mm, 30 mil/0.7mm
Finish	UV-Urethane with Ceramic Bead
Color	FloorFX Film Library
Size	Standard: 7" x 48" Custom Sizes: 9" x 48", 12" x 24"
Installation Method	Loose-Lay
Adhesive	Premium Pressure Sensitive Acrylic-base Adhesive
Warranty	Limited 10 Year Commercial

TEST DATA

Classification	ASTM F-1700	Class III, Type A or Type B Solid Vinyl Floor Tile
Thickness - Overall	ASTM F386-02(08)	Passes
Thickness - Wear Layer	ASTM F410-13	Passes
Size	ASTM F2055-10	Passes
Squareness	ASTM F2055-10	Passes
Resistance to Chemicals	ASTM F925-02(08)	Passes
Resistance to Heat	ASTM F1514-03(08)	Passes
Resistance to Light	ASTM F1515-08	Passes
Dimension Stability	ASTM F2199-09	Passes
Residual Indentation	ASTM F-1914-07	Passes - 6.5% average, 6.8% maximum
Static Load	ASTM F-970-07	Passes
Impact Sound Transmission	ASTM E492-09/E989-06(2012)	71 IIC
Airborne Sound Transmission Loss	ASTM E90-09/E413-10	69 STC
Flexibility	ASTM F137-03(07)	Passes - No cracks or breaks
Slip Resistance (Ramp Test)	DIN 51130:2010	Angle: 12.2°, Rating: R10

Visit www.floorfx.com for more information.

Please note: all measurements are nominal.

© 2017 DirectSource International, Inc. FloorFX™ Luxury Vinyl Solutions, Repose Solid Loose Lay Vinyl™ are trademarks of DirectSource International, Inc.