

Technical Specifications

Perform Luxury Vinyl Flooring™ is the standard for quality, sustainability and durability in solid vinyl flooring. It's advanced ceramic bead finish ensures brilliant color and pattern definition, superior scratch and scuff resistance, and low maintenance.

FEATURES	SUGGESTED APPLICATIONS
<ul style="list-style-type: none"> • UV urethane with ceramic bead finish • High contact backing ensures excellent bond with adhesive • Inverse edge profile allows for some expansion while minimizing pressure points • Superior performance and durability • 100% waterproof 	Residential Homes Apartments, Condominiums Hospitality Health Care Commercial

PRODUCT DETAIL

Construction	3.0mm Solid Vinyl Flooring
Wear Layer	Standard: 22 mil/0.5mm Custom: 12 mil/0.3mm, 30 mil/0.7mm
Finish	UV-Urethane with Ceramic Bead
Color	FloorFX Film Library
Available Sizes	Standard: 6" x 48" (plank) / 12" x 24" (tile) Custom Sizes: 4" x 36", 7" x 48", 9" x 48", 9" x 60", 18" x 36"
Installation Method	Glue-down
Adhesive	Taylor Meta-Tec 2091, Taylor Meta-Tec 2098, Spray-Lock 6500
Warranty	Limited 15 Year Light Commercial; Limited 10 Year Commercial

TEST DATA

Classification	ASTM F-1700	Class III, Type A or Type B Solid Vinyl Floor Tile
Thickness - Overall	ASTM F386-02(08)	Passes - ±0.005"
Thickness - Wear Layer	ASTM F410-13	Passes
Size	ASTM F2055-10	Passes
Squareness	ASTM F2055-10	Passes - Maximum 0.015"
Resistance to Chemicals	ASTM F925-02(08)	Passes - No change
Resistance to Heat	ASTM F1514-03(08)	Passes
Resistance to Light	ASTM F1515-08	Passes
Dimension Stability	ASTM F2199-09	
Residual Indentation	ASTM F-1914-07	Passes - 0.085" average
Static Load	ASTM F-970-07	Passes - 0.007" maximum at 2000 psi
Flexibility	ASTM F137-03(07)	Passes - Mandrel diameter 1", no cracks or breaks
Coefficient of Friction	ASTM C 1028-2007	Dry: 0.70, Wet: 0.79

Visit www.floorfx.com for more information.